

RIVER MURRAY FLOW REPORT

Public I2 A2

Report #46/2016

Issued 10:00 am 2 December 2016

This supersedes the previous flow report issued by the Department of Environment, Water and Natural Resources (DEWNR) on 25 November 2016. The next report will be provided on Friday 9 December 2016.

In this report, for ease of representation, large volumes of water are expressed in gigalitres (GL), while smaller volumes are expressed in megalitres (ML). One GL is equal to 1 000 ML.

FLOW OUTLOOK

The flow at the South Australian border peaked at approximately 95 GL/day on 30 November 2016 and will decrease to around 65 GL/day during the coming week. For comparison, in 2011 the peak flow to South Australia was around 94 GL/day.

Below is a table of the predicted River Murray water levels (and predicted date of the peak) at a number of locations from Lock 6 to Murray Bridge based on the peak flow of 95 GL/day at the South Australian border and previous flood events. The predicted peak water levels and dates are provided as a guide only.

Location	River km	Normal Pool Level (m AHD)	Current level at 30/11/16 (m AHD)	Water level is currently	Predicted water level (m AHD)	Predicted date of peak	2011 High Water Level (m AHD)
Lock 6	619.8	19.25	20.10	rising	20.15	4 Dec	20.11
Renmark	567.4	-	-	rising	17.44	7 Dec	17.38
Lock 5	562.4	16.30	16.77	rising	17.07	7 Dec	17.05
Lyrup	537.8	-	15.37	rising	15.80	9 Dec	15.68
Berri	525.9	-	14.82	rising	15.27	9 Dec	15.16
Lock 4	516.2	13.20	14.40	rising	14.77	9 Dec	14.75
Loxton	489.9	-	13.07	rising	13.50	9 Dec	13.42
Cobdogla	446.9	-	-	rising	11.70	15 Dec	11.52
Lock 3	431.4	9.80	10.09	rising	11.00	16 Dec	10.93
Overland Corner	425.9	-	9.31	rising	10.33	17 Dec	10.27
Waikerie	383.6	-	8.00	rising	9.10	18 Dec	9.06
Lock 2	362.1	6.10	7.18	rising	8.30	19 Dec	8.25
Cadell	332.6	-	5.75	rising	6.90	20 Dec	6.82
Morgan	321.7	-	5.24	rising	6.30	20 Dec	6.20
Lock 1	274.2	3.20	3.50	rising	4.45	22 Dec	4.42
Swan Reach	245.0	0.75	2.15	rising	# 3.10	25 Dec	3.04
Mannum PS	149.8	0.75	0.99	rising	# 1.20	25 Dec	1.05
Murray Bridge	115.3	0.75	0.80	rising	# 1.10	25 Dec	1.01

Note: Water levels (in particular below Lock 1) can be affected by local wind conditions by approximately 0.3 m

Water levels based on limited data

Now is a great time to enjoy the River Murray. However visitors are reminded to exercise caution at all times when using the river and to seek local advice.



River Murray Flow Report

The flow to South Australia comprises the normal December Entitlement Flow of 7 GL/day (includes environmental water on SA licence) and unregulated flow.

The flow over Lock 1 is approximately 56 GL/day and will increase to around 61 GL/day during the coming week, depending on weather conditions and extractions.

It is important to note that flow forecasts in this advice are based on the information available at the time of preparation. Advice may change as new gauging information becomes available, or due to rainfall events or changed operations upstream. The forecasts will be revised as new information becomes available.

SAND BAGGING

As River Murray water levels increase, there will be inundation of some properties on the floodplain. The State Emergency Service (SES) is distributing sandbags to residents, businesses and shack owners from a number of local government locations. To access sand bags call one of the following councils:

- Mid Murray Council - call 8540 0060 for collection from Morgan, Blanchetown Mannum or Cambrai
- Rural City of Murray Bridge – call 8539 1100 for collection from Murray Bridge
- Coorong District Council – call 0429 900 919 for collection from Tailem Bend
- Renmark Paringa Council – call 8580 3000 for collection from Renmark
- Berri Barmera Council – call 8582 1922 for collection from Berri or Barmera
- District Council of Loxton Waikerie – call 8584 8040 for collection from Loxton
- call 8541 0740 for collection from Waikerie

ENVIRONMENTAL WATER

During December 2016 the Commonwealth Environmental Water Holder and the Murray-Darling Basin Authority's *The Living Murray* are providing environmental water to South Australia. The environmental water will provide in-channel, Lower Lakes and Coorong environmental and water quality benefits.

DEWNR is continuing discussions regarding environmental water to be delivered during 2016-17.

MURRAY MOUTH

Dredging operations at the Murray Mouth commenced on 9 January 2015 to maintain connectivity (exchange of water) between the Coorong and the Southern Ocean.

The dredging operations combined with recent substantial barrage releases have improved conditions at the Murray Mouth. One dredge is continuing to operate between the Tauwitchere and Goolwa channels. At 27 November 2016 approximately 1 733 800 cubic metres of sand had been removed by dredging operations.

Mariners are advised that there are still a number of shallow zones in and adjacent to the Murray Mouth and should follow all directions in the area and reduce their speed. Boats equipped with echo sounders should regularly check depths and avoid travelling at low tide. Mariners are reminded that navigation through the Murray Mouth is only permitted during daylight hours and that Exclusion Zones established around the dredging operations remain in place to ensure public safety. For more information, refer to the Notice to Mariners at <http://dpti.sa.gov.au/news/?a=247918>

There is also a partial park closure in place for the northern tip of the Coorong National Park. For more information refer to the following www.environment.sa.gov.au/parks/Safety/Park_closures/141219-coorong-national-park. Signage has been installed at appropriate locations advising of Exclusion Zones.



BARRAGE OPERATIONS AND WATER LEVELS IN THE LOWER LAKES

The water level in Lake Alexandrina is approximately 0.71 m AHD and Lake Albert approximately 0.67 m AHD. The difference in water levels is due to wind effects. Water levels are being actively managed to achieve a target water level of 0.8 m AHD at the end of December 2016.

Due to the unregulated flow event, when weather conditions are favourable, water is being released from the barrages into the Coorong. Releases are being prioritised at Tauwitchere, Goolwa, Ewe Island and Mundoo barrages. The primary aims of the releases are to reduce salinity levels in the Lower Lakes and scour sand from the Murray Mouth. All fishways are operational to provide fish passage between Lake Alexandrina and the Coorong.

During the week ending 29 November 2016 total barrage releases were approximately 300 GL.

During adverse weather conditions SA Water will operate the barrages to minimise the risk of seawater entering Lake Alexandrina, therefore minimising any negative salinity impacts from reverse flow events.

Water levels and barrage operations are monitored closely by South Australian Government agencies, the Murray-Darling Basin Authority and the Commonwealth Environmental Water Office.

WATER QUALITY - BLACKWATER

High flows across New South Wales and Victoria have mobilised large amounts of organic matter from the floodplain into the River Murray. The breakdown of organic matter consumes dissolved oxygen, which has led to low levels of oxygen in the water and a dark discolouration - known as blackwater.

The blackwater event is now in the South Australian portion of the River Murray.

Blackwater events occur naturally but when dissolved oxygen levels drop below critical levels it can cause fish and crustaceans to die. To report sightings of large numbers of dead or distressed fish contact the 24-hour FISHWATCH hotline on 1800 065 522.

SA Health has advised that blackwater in the River Murray poses no direct public health risk. In a small number of people, blackwater may cause a skin irritation due to sensitivity to natural organic matter in the water. SA Health does not recommend drinking water direct from the River Murray at any time unless it is treated.

SA Water has advised that the water quality challenges presented by blackwater can be effectively treated via SA Water's treatment processes and therefore do not currently pose a drinking water quality issue.

DEWNR, SA Water and Murray-Darling Basin Authority with other government agencies are working closely to monitor the situation.

WEIR POOL OPERATIONS

Due to high flows, the River Murray weirs have been temporarily opened (open river conditions). This is a standard operating procedure during periods of high flow. The weirs will be reinstated once the high flows recede.

LOXTON RIVER VESSEL WASTE DISPOSAL STATION

The Loxton River Vessel Waste Disposal Station was closed on 14 November 2016 and will remain closed until the high flows recede. The remaining 12 waste disposal stations operated by DEWNR will continue to be available for use up to 120 GL/day.

Due to the high flow conditions no alternative waste pumping service is available at Loxton. The nearest river vessel waste disposal stations are at Berri (38 km upstream) or Lock 3 (55 km downstream). For further information contact Hayden Smith (DEWNR) on 0457 820 553.

LOWER MURRAY LEVEE EMBANKMENTS

Between Mannum and Wellington there are approximately 118 kilometres of levee banks, of which 67 kilometres are managed and maintained by the South Australian Government.

All Government-managed levee banks have had an intensive condition assessment undertaken (prior to the peak flow). A final survey of the levees will occur on Monday 5 December 2016. If landholders have specific concerns about the Government-managed levee banks they can contact Mr Said Khelwaty, Project Engineer on 0434 076 515 or said.khelwaty@sa.gov.au.

The 2010 digital elevation data of levees (Government and private) can still be accessed under the Levee Profile Mapping section on the Water Connect website at www.waterconnect.sa.gov.au/River-Murray

For any general advice or other questions relating to government or privately owned levee banks you can contact Mr Richard Brown, Infrastructure Operations Manager on 0412 046 777 or richard.brown@sa.gov.au.

NAVIGATION ISSUES

While this is a great time to visit the river, all visitors are reminded to exercise caution when navigating through the locks and 'opened' weirs, and to be mindful of partially submerged infrastructure such as jetties and floating debris. The higher flow may present a hazard to watercraft with low-horsepower engines.

Sandbars in the vicinity of the Murray Mouth may cause navigation hazards. Mariners are advised to navigate with caution when operating in the area. Sandbars are also present along sections of the River Murray downstream of Locks 7 and 8 and in South Australia. All watercraft users should be aware of the risk of submerged navigation hazards, and should regularly check river depth.

RIVER HAZARDS

After water levels peak, they could decrease by up to 0.3 m/day. People need to be aware of the likely rapid decrease and should take any necessary actions to modify pontoons and moorings.

Boaters are advised that current and forecast high flow conditions on the River Murray are causing inundation of riverbanks and associated structures.

Some boat launching facilities may become unserviceable due to changed river levels. Bridge clearances will also be reduced by rising water levels. Boaters should exercise caution when operating vessels near to the banks of the river or under bridges, and be aware of structures on, or near, the riverbank which may be submerged. Boaters are also likely to encounter floating debris which may cause damage to vessels or injury to water skiers.

Property owners who are likely to have submerged infrastructure (such as jetties) projecting into the river are reminded to attach a floating marker, coloured Yellow, to the extremity of the infrastructure. This will assist boat users to avoid colliding with the submerged structures.

Persons intending to engage in high speed activities should ensure that the area of water is safe prior to commencing the activity. Vessel wash should be kept to a minimum if operating in the vicinity of inundated houses and other buildings.

For more information, contact Department of Planning, Transport and Infrastructure Marine Operations on 1300 183 046.

RIVER MURRAY WATER LEVELS

Below is a table of River Murray water levels at a number of locations from Lock 10 (near Wentworth) to Murray Bridge.

River Murray Water Levels on 30 November 2016

Location	River km	Normal Pool Level (m AHD)	Current Level (m AHD)	1974 Flood Level (m AHD)	1993 Flood Level (m AHD)	2011 High Water Level (m AHD)
Lock 10	825.0	30.80	32.66	33.81	33.32	32.28
Lock 9 Kulnine	764.8	27.40	28.85	30.03	29.44	28.80
Lock 8 Wangumma	725.7	24.60	-	27.60	27.19	26.79
Lock 7 Rufus River	696.6	22.10	-	25.70	25.24	24.92
Lock 6 Murtho	619.8	19.25	20.10	21.03	20.50	20.11
Renmark	567.4	-	-	18.54	18.04	17.38
Lock 5	562.4	16.30	16.77	18.07	17.50	17.05
Lyrup	537.8	-	15.37	16.85	16.26	15.68
Berri	525.9	-	14.82	15.81	15.74	15.16
Lock 4	516.2	13.20	14.40	15.65	15.08	14.75
Loxton	489.9	-	13.07	15.05	14.12	13.42
Cobdogla	446.9	-	-	13.44	12.38	11.52
Lock 3	431.4	9.80	10.09	13.16	12.02	10.93
Overland Corner	425.9	-	9.31	12.73	11.58	10.27
Waikerie	383.6	-	8.00	11.26	10.24	9.06
Lock 2	362.1	6.10	7.18	10.28	9.30	8.25
Cadell	332.6	-	5.75	9.17	8.08	6.82
Morgan	321.7	-	5.24	8.85	7.65	6.20
Lock 1 Blanchetown	274.2	3.20	3.50	6.81	5.38	4.42
Swan Reach	245.0	0.75	2.15	6.06	4.51	3.04
Mannum PS	149.8	0.75	0.99	3.15	1.90	1.05
Murray Bridge	115.3	0.75	0.80	2.06	1.26	1.01

Note that the above water levels may be affected by local wind conditions.

River Murray Flow Report

FURTHER INFORMATION

The WaterConnect website is South Australia's comprehensive water information portal and can be accessed at www.waterconnect.sa.gov.au

Up-to-date River Murray salinity, flow and water level information can be accessed at the Department of Environment, Water and Natural Resources, SA Water and Murray-Darling Basin Authority websites

- www.environment.sa.gov.au/managing-natural-resources/river-murray/water-allocation-and-trade/water-allocations-and-announcements
- www.waterconnect.sa.gov.au/Systems/RTWD/Pages/Default.aspx
- www.sawater.com.au/SAWater/Environment/WaterProofingAdelaide/TheRiverMurray/RMOU/Dailyflow.htm
- <http://livedata.mdba.gov.au/>

The latest news, information and announcements about the River Murray and Basin Plan are available at [River Murray Update](#).

The Department of Environment, Water and Natural Resources has published a series of inundation maps for the River Murray. They are available at www.waterconnect.sa.gov.au/Systems/RMIM/SitePages/Home.aspx

Information on the management of acid drainage water in the Lower River Murray can be accessed at www.epa.sa.gov.au/environmental_info/water_quality/programs/acid_sulfate_soils/lower_river_murray_reclaimed_irrigation_area_lmria

Details of river height and rainfall information in the River Murray within Victoria and New South Wales are available at the Bureau of Meteorology website www.bom.gov.au/vic/flood

Information provided by the Commonwealth Environmental Water Office can be accessed at www.environment.gov.au/ewater/southern/murray/lower-murray.html

Information on The Living Murray can be accessed at www.mdba.gov.au/managing-water/environmental-water/delivering-environmental-water/living-murray-program

Chowilla Floodplain Icon Site management www.environment.sa.gov.au/Chowilla-floodplain

Department of Environment, Water and Natural Resources www.environment.sa.gov.au/Home

Information provided by the Department of Planning, Transport and Infrastructure on boat licences, registering motor boats, owning and operating water craft, and boat and marine safety can be accessed at www.sa.gov.au/boatingmarine

ID	RM-Flow-Report 20161202
Classification	Public I2 A2
Issued	2 December 2016
Authority	DEWNR
Master Document Location	Q:\OMP\RM REM\02 RM Ops\04 Communications\Flow Advices\2016-17
Managed and Maintained by	River Murray Operations
Author	River Murray Operations
Reviewer	Director River Murray Operations, Strategy and Advice