

RIVER MURRAY FLOW REPORT

Public I2 A2

Report #43/2013

Issued 10:00 am 1 November 2013

This supersedes the previous flow report issued by the Department of Environment, Water and Natural Resources (DEWNR) on 25 October 2013. The next flow report will be provided on Friday, 8 November 2013.

FLOW OUTLOOK

The flow at the South Australian border is approximately 12 000 ML/day and will remain around this rate during the coming week, depending on upstream river and storage operations, extractions, and rainfall events. The flow comprises the November Entitlement Flow of 6 000 ML/day plus environmental water from The Living Murray and Commonwealth Environmental Water Holder. South Australia will continue to receive substantial volumes of environmental water in November and December 2013. The environmental water will:

- maintain a flow at the border higher than normal Entitlement Flow;
- manage the rate of recession;
- provide for environmental outcomes in the Coorong; and
- provide in-channel benefits.

The flow over Lock 1 is approximately 12 500 ML/day and will reduce to around 9 500 ML/day during the coming week, depending on weather conditions and extractions.

It is important to note that flow forecasts in this advice are based on the information available at the time of preparation. They may change as new gauging information becomes available, or due to rainfall events or changed operations upstream. Flow forecasts are dependent on predictions made by the Bureau of Meteorology, Murray-Darling Basin Authority and water management agencies in upstream jurisdictions. They will be revised as new information becomes available.

BARRAGE OPERATIONS AND WATER LEVELS IN THE LOWER LAKES

The water level in Lake Alexandrina is approximately 0.76 m AHD and approximately 0.71 m AHD in Lake Albert. During the coming fortnight, barrage operations will target a water level of 0.80 m AHD in both Lakes, which should assist in maintaining barrage releases for longer periods in the coming months. Barrage releases are being prioritised through the Tauwichee and Goolwa barrages to maintain an open and functioning Murray Mouth, promote native fish migration and manage Coorong water levels for ecological outcomes. All barrage fishways are in operation and are being supplemented with attractant flows in adjacent bays. SA Water will continue to operate the barrages to minimise any negative salinity impacts from reverse flow events during these conditions.

To see live salinity data at various locations on the River Murray and in the Lower Lakes, please refer to the following website: <http://www.waterconnect.sa.gov.au/Systems/RTWD/SitePages/Home.aspx>

Water levels and barrage operations are monitored closely by various agencies of the South Australian Government, Murray-Darling Basin Authority and Commonwealth Environmental Water Office.

NAVIGATION ISSUES

Sandbars in the vicinity of the Murray Mouth may cause navigation hazards. Mariners are advised to navigate with caution when operating in the area. Sandbars are also present along sections of the River Murray in South Australia and all watercraft users should be aware of, and regularly check, the river depth.



CONSTRUCTION WORKS

Currency Creek

Subject to confirmation by the Commonwealth Government under the Environment Protection and Biodiversity Conservation Act 1999 (Cwlth), water-based works to remove the Currency Creek Regulator are completed. The boating exclusion zone has been removed. The site has a few items of plant and equipment remaining, and a stockpile of rock material that was removed from the regulator. These will be removed when weather conditions improve to enable access.

Chowilla

Construction of the Chowilla Creek Environmental Regulator and associated structures is ongoing. For public safety reasons the Chowilla Creek remains closed to navigation at the construction site. Works are also underway to upgrade the weirs on Pipeclay Creek and Slaney Creek to improve the management of flows into the Chowilla anabranch and to enable fish passage. Public access around the weirs is restricted during this construction program.

RIVER MURRAY WATER LEVELS

Below is a table of River Murray water levels at a number of locations from Lock 10 (near Wentworth) to Murray Bridge.

River Murray Water Levels on 30 October 2013

Location	River km	Normal Pool Level	Current Level (m AHD)	1974 Flood Level (m AHD)	1993 Flood Level (m AHD)
Lock 10	825.0	30.80	30.85	33.81	33.32
Lock 9 Kulnine	764.8	27.40	27.51	30.03	29.44
Lock 8 Wangumma	725.7	24.60	24.96	27.60	27.19
Lock 7 Rufus River	696.6	22.10	22.09	25.70	25.24
Lock 6 Murtho	619.8	19.25	19.25	21.03	20.50
Renmark	567.4	-	16.36	18.54	18.04
Lock 5	562.4	16.30	16.34	18.07	17.50
Lyrup	537.8	-	13.35	16.85	16.26
Berri	525.9	-	13.27	15.81	15.74
Lock 4	516.2	13.20	13.25	15.65	15.08
Loxton	489.9	-	10.45	15.05	14.12
Cobdogla	446.9	-	9.95	13.44	12.38
Lock 3	431.4	9.80	9.86	13.16	12.02
Overland Corner	425.9	-	6.53	12.73	11.58
Waikerie	383.6	-	6.38	11.26	10.24
Lock 2	362.1	6.10	6.08	10.28	9.30
Cadell	332.6	-	3.54	9.17	8.08
Morgan	321.7	-	3.42	8.85	7.65
Lock 1 Blanchetown	274.2	3.20	3.24	6.81	5.38
Swan Reach	245.0	0.75	0.91	6.06	4.51
Mannum PS	149.8	0.75	0.81	3.15	1.90
Murray Bridge	115.3	0.75	0.74	2.06	1.26

Note that the above water levels may be affected by local wind conditions.

River Murray Flow Report

FURTHER INFORMATION

The WaterConnect website is South Australia's comprehensive water information portal and can be accessed at: <http://www.waterconnect.sa.gov.au>

Up-to-date River Murray flow and water level information can be accessed at the Department of Environment, Water and Natural Resources, SA Water and Murray-Darling Basin Authority websites:

<http://www.waterconnect.sa.gov.au/Systems/RTWD/SitePages/Home.aspx>
www.sawater.com.au/SAWater/Environment/TheRiverMurray/River+Murray+Levels.htm
www.mdba.gov.au/water/live-river-data

The Department of Environment, Water and Natural Resources has published a series of inundation maps for the River Murray. They are available at: <http://www.waterconnect.sa.gov.au/Systems/RMIM/Pages/default.aspx>

Information on the management of acid drainage water in the Lower River Murray can be accessed online at: http://www.epa.sa.gov.au/environmental_info/water_quality/acid_sulfate_soils_ass/lower_river_murray_reclaimed_irrigation_area_lmria

Details of river height and rainfall information in the River Murray within Victoria and New South Wales are available at the Bureau of Meteorology website: <http://www.bom.gov.au/vic/flood>

Information provided by the Commonwealth Environmental Water Office can be accessed at: www.environment.gov.au/ewater/southern/murray/lower-murray.html

Information on The Living Murray can be accessed at: <http://www.mdba.gov.au/about-basin/environmental-sites>

Information is also available from the SA Water Hotline on **08 8595 2299**

Department of Environment, Water and Natural Resources
<http://www.environment.sa.gov.au/Home>

ID	RM-Flow-Report 20131101
Classification	Public I2 A2
Issued	1 November 2013
Authority	DEWNR
Master Document Location	Q:\OMP\RM REM\02 RM Ops\04 Communications\Flow Advices\2013-14
Managed and Maintained by	River Murray Operations
Author	River Murray Operations
Reviewer	Director River Murray Operations

