RIVER MURRAY FLOW REPORT and WATER RESOURCES UPDATE

Public I2 A2

Report #02/2015 Issued 10:00 am 16 January 2015

This supersedes the previous flow report issued by the Department of Environment, Water and Natural Resources (DEWNR) on 9 January 2015. The next flow report will be provided on Friday, 23 January 2015.

In this report, for ease of representation, large volumes of water are expressed in gigalitres (GL), while smaller volumes are expressed in megalitres (ML). One GL is equal to 1 000 ML.

WATER RESOURCES UPDATE

During December 2014, the total River Murray System inflow was approximately 160 GL, which is well below the December long-term average of 460 GL. Inflow to Menindee Lakes (from the Darling System) during December 2014 was 1 GL, which is well below the December long-term average of 120 GL.

The flow to South Australia during December 2014 was approximately 255 GL (compared to 375 GL in December 2013 and the December long-term average of 690 GL). The flow comprised:

- 217 GL of December Entitlement Flow; and
- approximately 38 GL of environmental water from The Living Murray program and Commonwealth Environmental Water Holder.

STORAGE VOLUMES

Murray-Darling Basin storage volumes at 14 January 2015 and 14 January 2014


Storage	Full Supply Volume	14/01/2015	14/01/2014	Long-term average
	(GL)	(GL)	(GL)	(end of January)
Dartmouth	3 856	3 185 (83%)	3 618 (94%)	
Hume	3 003	1 598 (53%)	1 965 (65%)	
Lake Victoria	677	470 (69%)	600 (89%)	
Menindee Lakes	1 731*	185**(11%)	613 (35%)	
TOTAL	9 267	5 438 (59%)	6 796 (73%)	6 343 (74%)

^{*}Menindee Lakes can be surcharged to 2 015 GL

MENINDEE LAKES

Under the Murray-Darling Basin Agreement, the Murray-Darling Basin Authority controls the Menindee Lakes until the stored water volume decreases to 480 GL. The New South Wales Government assumes control of the storage at 480 GL and maintains control until the volume in storage exceeds 640 GL. On 18 February 2014, the volume in the Menindee Lakes decreased to below 480 GL and control switched to the New South Wales Government.

Given that the Menindee Lakes remain under New South Wales control, there is less flexibility in the way water can be delivered to South Australia in 2015, unless the storage position improves significantly.





^{**}Menindee Lakes are now under New South Wales control

RAINFALL AND TEMPERATURE OUTLOOK

The latest Bureau of Meteorology weather outlook for January to March 2015 indicates a roughly equal chance of experiencing a wetter or drier season over the Murray-Darling Basin with temperatures likely to be warmer than normal.

Climate influences include El Niño-like conditions in the tropical Pacific Ocean, and warmer than normal waters across the Indian Ocean and to the southeast of Australia.

For the latest forecast on the likelihood of El Niño establishing in 2015, please refer to the following website: http://www.bom.gov.au/climate/enso/

WATER QUALITY - Salinity

A number of targets are identified under the Basin Plan, which all Basin States must have regard to in managing River Murray flows. The targets for real-time salinity are identified below. Salinity must not exceed these values for 95 per cent of the time:

- 580 EC at Lock 6
- 800 EC at Morgan
- 830 EC at Murray Bridge
- 1 000 EC at Milang

The following graph shows the salinity at these locations and the flow to South Australia from January 2014 to January 2015. The dashed-lines identify the Basin Plan thresholds for the corresponding colour coded location. It confirms that salinity has not exceeded the threshold at any of these four locations during this period.

SA River Murray Daily Average Salinity



FLOW OUTLOOK

The flow at the South Australian border is approximately 8.0 GL/day and will increase to around 8.4 GL/day during the coming week, depending on upstream river and storage operations, extractions, and rainfall events. The flow comprises the normal January Entitlement Flow of 7 GL/day plus environmental water from the Commonwealth Environmental Water Holder (CEWH). The environmental water is being delivered to provide in-channel, Lower Lakes and Coorong environmental benefits and assist in discharging salt through the Murray Mouth. South Australia is working with the CEWH to seek further opportunities to deliver environmental water during summer.

The flow over Lock 1 is approximately 7.5 GL/day and will reduce to around 5.5 GL/day during the coming week, depending on weather conditions and extractions.

It is important to note that flow forecasts in this advice are based on the information available at the time of preparation. They may change as new gauging information becomes available, or due to rainfall events or changed operations upstream. Flow forecasts are dependent on predictions made by the Bureau of Meteorology, Murray-Darling Basin Authority and water management agencies in upstream jurisdictions. They will be revised as new information becomes available.

WATER TRADE FROM THE MURRUMBIDGEE RIVER VALLEY REOPENED

On 12 January 2015, New South Wales Department of Primary Industries announced the resumption of water trade out of the Murrumbidgee Valley.

MANAGEMENT OF SOUTH AUSTRALIA'S DEFERRED WATER

The Murray-Darling Basin Authority advised that on 1 January 2015, South Australia had 42.8 GL of water deferred and stored in Dartmouth (29.5 GL for critical human water needs and 13.3 GL for private carryover use in future dry years). Volumes stored are adjusted for net evaporation losses until delivered to South Australia.

DEWNR is investigating opportunities to defer additional Entitlement Flow during 2014-15.

MURRAY MOUTH

Dredging operations at the Murray Mouth commenced on 9 January 2015 to maintain connectivity (exchange of water) between the river and the Southern Ocean.

Exclusion Zones have been established around the dredging operations to ensure public safety. For more information refer to the Notice to Mariners at:

http://webapps.transportsa.com.au/news/templates/dtei_template2010.aspx?articleid=2865&zoneid=15

There is also a partial park closure in place for the northern tip of the Coorong National Park. For more information refer to the following:

http://www.environment.sa.gov.au/parks/Safety/Park closures/141219-coorong-national-park

Signage has been installed at appropriate locations and flyers have been distributed advising of Exclusion Zones.

Any boats navigating through the Murray Mouth region should proceed with caution due to sandbars being present at shallow depth. Boats equipped with 'echo sounders' are strongly encouraged to regularly check depths.

BARRAGE OPERATIONS AND WATER LEVELS IN THE LOWER LAKES

The water level in Lake Alexandrina is approximately 0.61 m AHD and Lake Albert is approximately 0.65 AHD. Localised rainfall over the past week has increased water levels within the Lower Lakes. When conditions are favourable, barrage releases of approximately 1 GL/day will be prioritised through Tauwitchere and Goolwa



(approximately 70:30 ratio), adjacent to the fishways. SA Water will continue to operate the barrages to minimise any negative salinity impacts from reverse flow events. All fishways are operating.

To see live salinity data at various locations on the River Murray and in the Lower Lakes, please refer to the following website: http://www.waterconnect.sa.gov.au/Systems/RTWD/SitePages/Home.aspx

Water levels and barrage operations are monitored closely by various agencies of the South Australian Government, Murray-Darling Basin Authority and Commonwealth Environmental Water Office.

WEIR POOL OPERATIONS

The Lock 1 and Lock 2 weir pool raising event is complete. Lock 1 is 0.10 m below normal pool level of 3.2 m to enable investigations to be undertaken at the weir.

NAVIGATION ISSUES

Sandbars in the vicinity of the Murray Mouth may cause navigation hazards. Mariners are advised to navigate with caution when operating in the area. Sandbars are also present along sections of the River Murray, downstream of Lock 7 and 8 and in South Australia. All watercraft users should be aware of the risk of submerged navigation hazards, and should regularly check river depth.

CONSTRUCTION WORKS

Lock 7 – advanced notice

Remedial works at Lock 7 are expected to commence after the Australia Day long weekend in January 2015 and take around 12 weeks to complete. The works are necessary to maintain the structural integrity of the Lock chamber. During this period Lock 7 will be closed to navigation.

Pike Floodplain

Construction works are underway at Bank B and C on the Pike Floodplain to reinstate fish passage and hydraulic connectivity between the River Murray and Mundic Creek. Works are expected to be ongoing until July 2015. This activity will not cause restrictions to navigation on the main channel of the River Murray. Mundic Creek Road will be closed while works are underway.

Yatco Lagoon

Work is underway to relocate pump offtakes from Yatco Lagoon and install new pump offtakes on the River Murray. The construction work is expected to be completed by mid-2015.



RIVER MURRAY WATER LEVELS

Below is a table of River Murray water levels at a number of locations from Lock 10 (near Wentworth) to Murray Bridge.

River Murray Water Levels on 14 January 2015

Location	River km	Normal Pool Level	Current Level	1974 Flood Level	1993 Flood Level
			(m AHD)	(m AHD)	(m AHD)
Lock 10	825.0	30.80	30.82	33.81	33.32
Lock 9 Kulnine	764.8	27.40	27.36	30.03	29.44
Lock 8 Wangumma	725.7	24.60	24.56	27.60	27.19
Lock 7 Rufus River	696.6	22.10	22.10	25.70	25.24
Lock 6 Murtho	619.8	19.25	19.26	21.03	20.50
Renmark	567.4	-	-	18.54	18.04
Lock 5	562.4	16.30	16.34	18.07	17.50
Lyrup	537.8	-	13.31	16.85	16.26
Berri	525.9	-	13.24	15.81	15.74
Lock 4	516.2	13.20	13.25	15.65	15.08
Loxton	489.9	-	10.21	15.05	14.12
Cobdogla	446.9	-	9.94	13.44	12.38
Lock 3	431.4	9.80	9.89	13.16	12.02
Overland Corner	425.9	-	6.35	12.73	11.58
Waikerie	383.6	-	6.29	11.26	10.24
Lock 2	362.1	6.10	6.16	10.28	9.30
Cadell	332.6	-	-	9.17	8.08
Morgan	321.7	-	3.22	8.85	7.65
Lock 1 Blanchetown	274.2	3.20	3.12	6.81	5.38
Swan Reach	245.0	0.75	0.91	6.06	4.51
Mannum PS	149.8	0.75	0.84	3.15	1.90
Murray Bridge	115.3	0.75	0.65	2.06	1.26

Note that the above water levels may be affected by local wind conditions.

FURTHER INFORMATION

The WaterConnect website is South Australia's comprehensive water information portal and can be accessed at: http://www.waterconnect.sa.gov.au

Up-to-date River Murray flow and water level information can be accessed at the Department of Environment, Water and Natural Resources, SA Water and Murray-Darling Basin Authority websites:

http://www.waterconnect.sa.gov.au/Systems/RTWD/SitePages/Home.aspx

http://www.sawater.com.au/SAWater/Environment/WaterProofingAdelaide/TheRiverMurray/RMOU/Dailyflow.htm http://www.mdba.gov.au/river-data/live-river-data

The Department of Environment, Water and Natural Resources has published a series of inundation maps for the River Murray. They are available at: http://www.waterconnect.sa.gov.au/Systems/RMIM/Pages/default.aspx

Information on the management of acid drainage water in the Lower River Murray can be accessed online at: http://www.epa.sa.gov.au/environmental info/water quality/acid sulfate soils ass/lower river murray reclaimed irrigation_area_lmria

Details of river height and rainfall information in the River Murray within Victoria and New South Wales are available at the Bureau of Meteorology website: http://www.bom.gov.au/vic/flood

Information provided by the Commonwealth Environmental Water Office can be accessed at: www.environment.gov.au/ewater/southern/murray/lower-murray.html

Information on The Living Murray can be accessed at: http://www.mdba.gov.au/about-basin/environmental-sites

Department of Environment, Water and Natural Resources http://www.environment.sa.gov.au/Home

ID	RM-Flow-Report 20150116
Classification	Public I2 A2
Issued	16 January 2015
Authority	DEWNR
Master Document Location	Q:\OMP\RM REM\02 RM Ops\04 Communications\Flow Advices\2014-15
Managed and Maintained by	River Murray Operations
Author	River Murray Operations
Reviewer	Director River Murray Operations and Major Projects