Southern Basins PWA Uley Wanilla

2017 Groundwater level and salinity status report



Department for Environment and Water GPO Box 1047, Adelaide SA 5001

Telephone National (08) 8463 6946

International +61 8 8463 6946

Fax National (08) 8463 6999

International +61 8 8463 6999

Website <u>www.environment.sa.gov.au</u>

Disclaimer

The Department for Environment and Water and its employees do not warrant or make any representation regarding the use, or results of the use, of the information contained herein as regards to its correctness, accuracy, reliability, currency or otherwise. The Department for Environment and Water and its employees expressly disclaims all liability or responsibility to any person using the information or advice. Information contained in this document is correct at the time of writing.



This work is licensed under the Creative Commons Attribution 4.0 International License.

To view a copy of this license, visit http://creativecommons.org/licenses/by/4.0/

© Crown in right of the State of South Australia, through the Department for Environment and Water 2018

ISBN 978-1-925805-20-8

Preferred way to cite this publication

DEW (2018). Southern Basins PWA Uley Wanilla 2017 Groundwater level and salinity status report, Government of South Australia, Department for Environment and Water, Adelaide.

Download this document at www.waterconnect.sa.gov.au

2017 Status summary Southern Basins PWA Uley Wanilla



The Uley Wanilla lens of the Southern Basins Prescribed Wells Area (PWA) has been assigned a *yellow* status for 2017 because minor adverse trends have been observed over the past five years.

The status is based on five-year trends: over the period 2013–17, 93% of wells show declining groundwater levels and 86% show stable salinities.

This status report does not seek to evaluate the sustainable limits of the resource, nor does it make any recommendations on management or monitoring of the resource. These actions are important, but occur through separate processes such as prescription and water allocation planning.

Rainfall

See Figures 1 and 2

Rainfall station	Big Swamp Bureau of Meteorology (BoM) rainfall station 18017, located approximately 3 km east of Uley Wanilla
Annual total ¹	476 mm 47 mm (9%) less than the five-year average of 523 mm 83 mm (15%) less than the long-term average of 559 mm
Monthly summary	Well-above average rainfall recorded in September, December and January Well-below average rainfall recorded in August, November, March through to June
Spatial distribution	Rainfall in 2016–17 was below average across the entire PWA

Water use

See Figure 3

Total allocated volume: 2016–17	224 ML
Licensed groundwater extractions*	107 ML ² (48% of total allocation)
Extraction volume comparison	29% greater than the previous year 36% greater than the five-year average

^{*}Stock and domestic use is not included in licensed extractions

¹ For the water-use year 1 July 2016 to 30 June 2017

² Total licensed extractions are subject to change as extraction data have not yet been verified in full – see More information

Groundwater level

See Figure 4

Five-year trend: 2013–17	1 out of 14 wells (7%) shows a rising trend, at a rate of 0.02 m/y
	13 wells (93%) show declining trends, at rates of 0.02–0.19 m/y (median of 0.04 m/y); four of these wells show their lowest level on record

Groundwater salinity

See Figures 5 and 6

2017 salinity	380–744 mg/L All 7 wells (100%) show salinities less than 1000 mg/L
Five-year trend: 2013–17	6 out of 7 wells (86%) are stable 1 well (14%) shows an increasing trend, at a rate of 19 mg/L/y

Regional setting



The Southern Basins PWA is located within the Eyre Peninsula Natural Resources Management Region, at the southern-most part of the Eyre Peninsula between the townships of Port Lincoln and Coffin Bay. The groundwater resources are prescribed under South Australia's *Natural Resources Management Act 2004*, and a water allocation plan (WAP) provides for their sustainable use. The Uley Wanilla lens is situated in the northern-part of the Southern Basins PWA.

Within the Southern Basins PWA, there are two main water-bearing sedimentary sequences that overlie basement rocks: the Quaternary limestone aquifer and the underlying Tertiary sands aquifer. The Quaternary limestone aquifer, which is the focus of this report, comprises a generally thin veneer of aeolian sediments of the Bridgewater Formation and is continuous across the PWA. The main source of recharge to the Quaternary limestone aquifer is the direct infiltration of local rainfall while the direction of groundwater flow is predominantly toward the nearest coastline.

Groundwater levels and salinities in the Southern Basins PWA are highly dependent on recharge from rainfall, and any trends in groundwater level or salinity are primarily climate driven: below-average rainfall results in a reduction in recharge to the aquifers. Below-average summer rainfall can also result in increasing extractions, and both elements can cause the groundwater levels to decline and may cause salinities to increase. Conversely, above-average rainfall can result in increases in recharge, decreases in extractions and groundwater levels may rise and salinities may stabilise or decrease. Historical rainfall data indicate that trends of above or below-average rainfall can last for up to 40 years, and that high-intensity rainfall can result in greater and more-rapid water level responses (i.e. recharge).




Figure 1. Spatial distribution of (1) Long-term and (2) five-year average annual rainfall, and (3) annual rainfall³

³ Data sources: SILO Patched Point Dataset https://silo.longpaddock.qld.gov.au/ and BoM Australian Water Availability Project (https://silo.longpaddock.qld.gov.au/ and BoM Australian Water Availability Project (https://silo.longpaddock.qld.gov.au/ and BoM Australian Water Availability Project (https://silo.longpaddock.qld.gov.au/ and BoM Australian Water Availability Project (https://www.bom.gov.au/ [sp. availabili




Figure 2. Annual and monthly rainfall for the past five water-use years recorded at Big Swamp (BoM Station 18017)⁴




Figure 3. Licensed groundwater extraction volumes⁵ for the past five water-use years

⁴ Data source: SILO Patched Point Dataset, available https://silo.longpaddock.qld.gov.au/ – see More information

⁵ Total licensed extractions are subject to change as extraction data have not yet been verified in full – see More information




Figure 4. Five-year trends (2013–17) in groundwater levels: Uley Wanilla lens




Figure 5. 2017 groundwater salinities: Uley Wanilla lens




Figure 6. Five-year trends (2013–17) in groundwater salinities: Uley Wanilla lens

More information

To determine the status of the Uley Wanilla lens for 2017, the trends in groundwater levels and salinities over the past five years (2013 to 2017, inclusive) were analysed, in contrast to the year-to-year assessments that have been used in *Groundwater level and salinity status reports* published prior to 2015. Please visit the Frequently Asked Questions on the *Water Resource Assessments* page on WaterConnect for more detail on the current method of evaluating the status of groundwater resources.

To view descriptions for all status symbols, and to review the full historical record of the monitoring wells, please visit the *Water Resource Assessments* page on WaterConnect.

For additional information related to monitoring wells nomenclature, please refer to the *Well Details* page on WaterConnect.

Consumptive pool is defined as the water that will, from time to time, be taken to constitute the resource within a particular part of a prescribed water resource. For further information please see the *Water Allocation Plan for the Southern Basins and Musgrave Prescribed Wells Areas* on the Natural Resources Eyre Peninsula website.

The licensed groundwater use for the 2016–17 water-use year is based on the best data available as of January 2018 and may be subject to change, as some extraction volumes may be in the process of being verified.

For information completeness and consistency across all the groundwater level and salinity status reports, the legend on each map herein shows the full range of water level and salinity status that could possibly be reported. However, the measured data that appear on each map may not span this full range.

Rainfall data used in this report is sourced from the SILO Patched Point Dataset, which uses original BoM daily rainfall measurements and is available online at https://silo.longpaddock.qld.gov.au/. Rainfall maps have been compiled using daily gridded data produced by the BoM Australian Water Availability Project (www.bom.gov.au/jsp/awap/).

To view the Southern Basins PWA Groundwater Level and Salinity Status Report 2009–10, which includes background information on hydrogeology, rainfall and relevant groundwater-dependent ecosystems, please visit WaterConnect. To view all past published Groundwater level and salinity status reports, please visit the Water Resource Assessments page on WaterConnect.

To download groundwater level and salinity data from monitoring wells within the Southern Basins PWA, please visit the *Groundwater Data* page under the *Data Systems* tab on <u>WaterConnect</u>.

For further details about the Southern Basins PWA, please see the *Water Allocation Plan for the Southern Basins and Musgrave Prescribed Wells Areas* on the Natural Resources Eyre Peninsula website.

Units of Measurement

mm millimetre

ML megalitre

m/y metres per year

mg/L milligrams per litre

mg/L/y milligrams per litre per year

mm/y millimetres per year

