RIVER MURRAY FLOW REPORT

Public I2 A2

Report #22/2017 Issued 10:00 am 2 June 2017

This supersedes the previous flow report issued by the Department of Environment, Water and Natural Resources (DEWNR) on 26 May 2017. The next report will be provided on Friday 9 June 2017.

In this report, for ease of representation, large volumes of water are expressed in gigalitres (GL), while smaller volumes are expressed in megalitres (ML). One GL is equal to 1 000 ML.

FLOW OUTLOOK

The flow at the South Australian border is approximately 5 GL/day and will decrease to around 4 GL/day during the coming week. It comprises:

- normal June Entitlement Flow 3 GL/day
- plus environmental water, and
- interstate trade adjustments.

The flow over Lock 1 is approximately 5.7 GL/day and will decrease to around 3 GL/day during the coming week, depending on weather conditions and extractions.

It is important to note that flow forecasts in this advice are based on the information available at the time of preparation. Advice may change as new gauging information becomes available, or due to rainfall events or changed operations upstream. The forecasts will be revised as new information becomes available.

ENVIRONMENTAL WATER

During June, approximately 56 GL of environmental water will be delivered to South Australia. The environmental water will provide in-channel, Lower Lakes and Coorong environmental and water quality benefits.

DEWNR is continuing discussions regarding environmental water to be delivered during 2017-18.

MURRAY MOUTH

Dredging operations at the Murray Mouth commenced on 9 January 2015 to maintain connectivity (exchange of water) between the Coorong and the Southern Ocean.

One dredge is operating in the Goolwa and Tauwitchere channels (currently operating in Goolwa channel). As at 28 May 2017, a total of approximately 1 994 100 cubic metres of sand had been removed by dredging operations.

As a result of Lake Victoria spilling in May, additional water was delivered to the Murray Mouth between 18 and 23 May to provide scouring flows. Most of this water was released from the Goolwa Barrage to maximise the scouring effect. The weather conditions were conducive to the operation. Monitoring has identified that this operation was successful in removing accumulated sand. Similar operations will be undertaken in the future.

Mariners are advised that there are still a number of shallow zones in and adjacent to the Murray Mouth. They should follow all directions in the area and reduce their speed. Boats equipped with echo sounders should regularly check depths and avoid travelling at low tide. Mariners are reminded that navigation through the Murray Mouth is only permitted during daylight hours and that Exclusion Zones established around the dredging operations are in place to ensure public safety. Refer to Notice to Mariners No 42 of 2016 www.dpti.sa.gov.au/news?a=287322

There is a partial park closure in place for the northern tip of the Coorong National Park. For more information visit <u>www.environment.sa.gov.au/parks/Safety/Park_closures/141219-coorong-national-park.</u>



River Murray Flow Report

BARRAGE OPERATIONS AND WATER LEVELS IN THE LOWER LAKES

The water level in Lake Alexandrina is approximately 0.67 m AHD and Lake Albert is approximately 0.66 m AHD. The difference in water levels is due to wind effects. Water levels are being managed to achieve a target water level of at least 0.6 m AHD by the end of June 2017.

During the week ending 30 May 2017 total barrage releases were approximately 3 GL. The reduced volume of barrage releases was due to adverse weather conditions (high tides, swells and winds). During adverse weather conditions SA Water will operate the barrages to minimise the risk of seawater entering Lake Alexandrina, therefore minimising any negative salinity impacts from reverse flow events. On 30 May, weather conditions became favourable, with additional barrages opened. Releases are being prioritised at Tauwitchere and Goolwa Barrages.

All fishways are operational and providing fish passage between Lake Alexandrina and the Coorong.

Water levels and barrage operations are monitored closely by the South Australian Government, the Murray-Darling Basin Authority and the Commonwealth Environmental Water Office.

WEIR POOL OPERATIONS (current)

The Lock 1 weir pool is approximately 0.1 m below the normal pool level of 3.2 m AHD to enable engineering works to be undertaken at the weir.

WEIR POOL OPERATIONS (Potential)

The Normal Pool Level (NPL) and Normal Operating Range for the South Australian locks and weirs are identified in the table below.

| Weir | Normal Pool Level (NPL) m AHD | Normal Operating Range (NOR) m AHD |
|--------------------------|----------------------------------|---------------------------------------|
| Lock 6 - Murtho | 19.25 | 19.17 - 19.50 |
| Lock 5 - Renmark | 16.30 | 16.22 - 16.43 |
| Lock 4 – Bookpurnong | 13.20 | 13.16 - 13.50 |
| Lock 3 - Overland Corner | 9.80 | 9.77 - 10.02 |
| Lock 2 – Waikerie | 6.10 | 6.02 - 6.40 |
| Lock 1 – Blanchetown | 3.20 | 3.10 - 3.50 |

Based on the success of previous weir pool raisings DEWNR is considering raising Lock 5 by approximately 45 cm above the NPL and Lock 2 by approximately 50 cm above the NPL in late winter to spring. These potential operations would raise Lock 5 to 16.75 m AHD (last year raised to 16.80 m AHD) and Lock 2 to 6.60 m AHD (last year raised to 6.85 m AHD).

Raising Lock 4 is also being considered in late winter to spring if high flows are experienced.

DEWNR is considering operation of the Chowilla Regulator in conjunction with raising Lock 6 raising to consolidate the benefits of the 2016 event.

Modest lowerings (within the normal operating ranges) are being investigated at Locks 2, 3, 5 and 6.

Further details of the proposed manipulations will be communicated in the coming weeks.

Weir pool manipulations aim to reinstate some of the natural variability of water levels in the River Murray system, which have been lost due to river regulation. The manipulations will assist to improve lateral connectivity, health, resilience and biodiversity of the river channel, floodplain and wetlands. It is intended that weir pool manipulations will become a routine part of river operations.



River Murray Flow Report

NAVIGATION ISSUES

Sandbars in the vicinity of the Murray Mouth may cause navigation hazards. Mariners are advised to navigate with caution when operating in the area. Sandbars are also present along sections of the River Murray downstream of Locks 7 and 8 and in South Australia. All Mariners should be aware of the risk of submerged navigation hazards, and should regularly check river depth.

RIVER MURRAY WATER LEVELS

Below is a table of River Murray water levels at a number of locations from Lock 10 (near Wentworth) to Murray Bridge.

| River multay water Levels | | | | | | | | |
|---------------------------|-------------|------------------------------------|--|-----------------------------------|-----------------------------------|--|--|--|
| Location | River km | Normal Pool Level (m AHD) | Current Level 31/5/2017 (m AHD) | 1974 Flood Level (m AHD) | 1993 Flood Level (m AHD) | 2016 High Water Level (m AHD) | | |
| Lock 10 | | (III AND) | | | (III AND) | | | |
| | 825.0 | 30.80 | 30.82 | 33.81 | 33.32 | 32.72 | | |
| Lock 9 Kulnine | 764.8 | 27.40 | 27.52 | 30.03 | 29.44 | 28.85 | | |
| Lock 8 Wangumma | 725.7 | 24.60 | 24.58 | 27.60 | 27.19 | 26.85 | | |
| Lock 7 Rufus River | 696.6 | 22.10 | 22.08 | 25.70 | 25.24 | 24.97 | | |
| Lock 6 Murtho | 619.8 | 19.25 | 19.26 | 21.03 | 20.50 | 20.19 | | |
| Renmark | 567.4 | - | 16.31 | 18.54 | 18.04 | 17.44 | | |
| Lock 5 | 562.4 | 16.30 | 16.30 | 18.07 | 17.50 | 17.05 | | |
| Lyrup | 537.8 | - | 13.24 | 16.85 | 16.26 | 15.80 | | |
| Berri | 525.9 | - | 13.23 | 15.81 | 15.74 | 15.21 | | |
| Lock 4 | 516.2 | 13.20 | 13.21 | 15.65 | 15.08 | 14.73 | | |
| Loxton | 489.9 | - | 10.09 | 15.05 | 14.12 | 13.54 | | |
| Cobdogla | 446.9 | - | 9.84 | 13.44 | 12.38 | 11.59 | | |
| Lock 3 | 431.4 | 9.80 | 9.81 | 13.16 | 12.02 | 10.98 | | |
| Overland Corner | 425.9 | - | 6.31 | 12.73 | 11.58 | 10.41 | | |
| Waikerie | 383.6 | - | 6.31 | 11.26 | 10.24 | 9.20 | | |
| Lock 2 | 362.1 | 6.10 | 6.14 | 10.28 | 9.30 | 8.32 | | |
| Cadell | 332.6 | - | 3.29 | 9.17 | 8.08 | 7.01 | | |
| Morgan | 321.7 | - | 3.22 | 8.85 | 7.65 | 6.38 | | |
| Lock 1 Blanchetown | 274.2 | 3.20 | 3.15 | 6.81 | 5.38 | 4.46 | | |
| Swan Reach | 245.0 | 0.75 | 0.69 | 6.06 | 4.51 | 3.11 | | |
| Mannum PS | 149.8 | 0.75 | 0.68 | 3.15 | 1.90 | 1.33 | | |
| Murray Bridge | 115.3 | 0.75 | 0.63 | 2.06 | 1.26 | 1.04 | | |

River Murray Water Levels

Note that the above water levels may be affected by local wind conditions.

3



River Murray Flow Report

FURTHER INFORMATION

The WaterConnect website is South Australia's comprehensive water information portal and can be accessed at www.waterconnect.sa.gov.au

Up-to-date River Murray salinity, flow and water level information can be accessed at the Department of Environment, Water and Natural Resources, SA Water and Murray-Darling Basin Authority websites

- <u>www.environment.sa.gov.au/managing-natural-resources/river-murray/water-allocation-and-trade/water-allocations-and-announcements</u>
- www.waterconnect.sa.gov.au/Systems/RTWD/Pages/Default.aspx
- <u>www.sawater.com.au/SAWater/Environment/WaterProofingAdelaide/TheRiverMurray/RMOU/Dailyflow.</u>
 <u>htm</u>
- <u>http://livedata.mdba.gov.au/</u>

The latest news, information and announcements about the River Murray and Basin Plan are available at <u>River Murray Update</u>.

The Department of Environment, Water and Natural Resources has published a series of inundation maps for the River Murray. They are available at www.waterconnect.sa.gov.au/Systems/RMIM/SitePages/Home.aspx

Information on the management of acid drainage water in the Lower River Murray can be accessed at <u>www.epa.sa.gov.au/environmental_info/water_quality/programs/acid_sulfate_soils/lower_river_murray_reclaime_d_irrigation_area_Imria</u>

Details of river height and rainfall information in the River Murray within Victoria and New South Wales are available at the Bureau of Meteorology website www.bom.gov.au/vic/flood

Information provided by the Commonwealth Environmental Water Office can be accessed at www.environment.gov.au/ewater/southern/murray/lower-murray.html

Information on The Living Murray can be accessed at www.mdba.gov.au/managing-water/environmental-water/delivering-environmental-water/living-murray-program

Chowilla Floodplain Icon Site management www.environment.sa.gov.au/Chowilla-floodplain

Department of Environment, Water and Natural Resources www.environment.sa.gov.au

Information provided by the Department of Planning, Transport and Infrastructure on boat licences, registering motor boats, owning and operating water craft, and boat and marine safety can be accessed at www.sa.gov.au/boatingmarine

| ID | RM-Flow-Report 20170602 | |
|---------------------------|--|--|
| Classification | Public I2 A2 | |
| Issued | 2 June 2017 | |
| Authority | DEWNR | |
| Master Document Location | Q:\OMP\RM REM\02 RM Ops\04 Communications\Flow Advices\2016-17 | |
| Managed and Maintained by | River Murray Operations | |
| Author | River Murray Operations | |
| Reviewer | Director River Murray Operations, Water | |

