

4 August 2010

Reference No. 107662007-011-L-Rev0

Mr Jai O'Toole  
Department for Water  
Level 1, 22 King William Street  
ADELAIDE SA 5000

## **RIVERBANK STABILITY RISK MANAGEMENT CALOOTE BOAT RAMP, SOUTH AUSTRALIA**

Dear Jai

### **Introduction**

Golder Associates Pty Ltd (Golder Associates) was requested by the Department for Water to assess the stability of the river bank near the boat ramp at Caloote, River Murray and to provide discussion on potential management and remedial options that might allow the ramp to be reopened.

Sinclair Knight Merz (SKM) previously undertook studies of potential for river bank collapse in the area on behalf of the Department of Water Land and Biodiversity Conservation (now Department of Water). These studies are described in SKM's report *Study into River Bank Collapsing for Lower Murray River* dated January 2010, which was reviewed by Golder Associates. Our report of that review was provided in document 107662007-002-Rev1 dated 16 February 2007.

The studies included intrusive investigations at Caloote and an assessment of the stability of two cross sections of the river bank. SKM's report indicates that the assessed stability of the riverbank, assuming a river water level of either -0.8m AHD and -1.5 m AHD, presented an unacceptable risk to human safety. The report recommended establishing an exclusion zone along the waterfront at Caloote which included the boat ramp area. This effectively precluded continued use of the boat ramp.

Lyndon Sanders, Principal Geotechnical Engineer, visited the Caloote boat ramp on 9 March 2010 and 17 June 2010 with Jai O'Toole of the Department for Water to gain an appreciation of the site conditions.

### **Scope of services**

Golder Associates reviewed the data collected by SKM at Caloote to assess the stratigraphy present near the boat ramp. On the basis of that review we performed check calculations of the river bank stability near the ramp. We considered options which might allow the boat ramp (although not necessarily the surrounding areas) to be reopened, which are discussed in the present report.

### **Scope of SKM Investigations**

The intrusive investigations carried out by SKM at Caloote included conducting a number of Cone Penetration Tests (CPT's). There are reports of ten CPT soundings conducted by EngTest and three



attempts at CPT soundings (at two locations previously tested by EngTest – CPT 3 and CPT 9) by Black Insitu Testing at Caloote.

SKM's investigations also included drilling four boreholes (Boreholes CA-BH1 to CA-BH4), with Boreholes CA-BH3 and CA-BH4 being located in the vicinity of the boat ramp.

The investigations also included laboratory testing on samples from the bores.

## **Boat Ramp stratigraphy**

Similar conditions were encountered in Boreholes CA-BH3 and CA-BH4. These boreholes indicated generally low strength clayey material to 17.5m and 11.5 m depth respectively, overlying higher strength (dense or very dense) granular material. In Borehole CA-BH3, a medium dense to dense granular layer was also present between 11.5 m and 12.5 m depth in the middle of lower strength clayey materials.

The CPTs conducted near the boat ramp (CPT's 6, and 9, with CPT's 7 and 10 slightly further away) suggest generally low strength material to at least 10 m depth. The Black Insitu Testing at CPT 9 (3 attempts) met refusal at between 5.5 m and 7 m depth, coinciding with a harder layer in the EngTest CPT 9 that is not readily correlated with the borehole observations.

Boreholes CA-BH3 and CA-BH4 are located some distance from the water's edge – as close, we suspect, as was reasonably practicable for drill rig access without significant temporary earthworks to provide a drilling platform or the use of a barge and overwater drilling.

SKM assumed – not unreasonably - that the stratigraphy would be consistent beyond Borehole CA-BH4 towards the River centreline.

Our review suggests that the stratigraphy adopted by SKM for its stability analyses was reasonable. There are some anomalies which it would be desirable to resolve – the difference in the depth to granular strata and the apparently stronger layer shown in the CPT tests. However, we recognise that this may not be practical – the stability assessments suggest that the risk (and cost?) of ground-based investigations near the River end of the boat ramp is likely to be unacceptable. The cost of overwater investigations is likely to be prohibitive.

## **Boat Ramp stability**

Our calculations gave similar results to SKM's and we conclude that the river bank at the boat ramp would not have acceptable stability (that is the calculated Factor of Safety would not be above 1.5) at water levels up to pool level (+0.75m AHD).

We therefore conclude that if the boat ramp is to be reopened, its stability will require improvement. This would imply improving the load carrying capacity of the soil by strengthening, reinforcing it or removing some of the load on the slope imposed by the boat ramp.

We also calculated the difference in stability between situations where the crest of the slope is loaded and unloaded (SKM assumed a 2.5 kPa surcharge load at the crest of the slope). The calculations suggest about 10% improvement in stability for the unloaded situation – calculated Factors of Safety around 1.35 and 1.5 for the loaded and unloaded situations assuming river water at pool level.

## **Stability improvement**

Based on the investigations performed to date, low strength clayey materials are likely to be present to around 18 m depth along the boat ramp alignment – to 17 m or more below river water level. This suggests that the scale of works needed to achieve an acceptable improvement in stability by earthworks (construction of buttresses or shear keys) is likely to be significant and probably impractical.

We expect that driving enough piles to strengthen the ground in the ramp area to prevent landsliding is likely to be difficult if not impossible. However, it would be possible to use piles to carry the traffic loads. This would reduce the risk of landsliding being triggered by trafficking, even if the stability of the ground itself was not greatly increased by the pile installation. In effect this new boat ramp would be a piled bridge which used the ground only as construction support. This option is likely to be feasible, if expensive.

Based on the stability analyses (both SKM's and Golder Associates'), we expect that piles would need to be placed starting approximately 50 m inland of the water's edge and extending some distance into the River. We expect that the piles would have to be at least 20 m long and would be capped with a structural slab. Pile spacing and slab thickness depend on each other, but 'back of envelope' estimates suggest a pile spacing of around 3 m and slab thickness of around 0.3 m. The final scheme would have to involve structural engineering design.

Even with a piled bridge in place there is still risk associated with trafficking of the river bank crest because if the land started to slide because the water level in the river dropped to a sufficiently low level, the piles would not be strong enough to hold the ground back and support the traffic loads. Therefore we expect that the boat ramp could only be used when the assessed stability of the unloaded river bank was acceptable.

Based on analyses presented by Richard Brown of the Department for Water at an emergency response planning meeting on 28 July 2010 the trigger level may be around 0.0 m AHD, at which level the Factor of Safety for the loaded riverbank is assessed by SKM to about 1.25. However, that would require confirmation by the various stakeholders, as the Factor of Safety for the unloaded river bank is likely to still be below 1.5.

This approach would require the river level to be monitored and a restriction placed on the use of the ramp during times when the river falls below the trigger level. We expect that enforcement of that restriction may be difficult or impractical.

There is some uncertainty as to the stratigraphy at the boat ramp. It would not be feasible to conduct on-land intrusive investigations closer to the river bank due to the safety risk management issues. Conducting intrusive investigations over-water near the bank edge would be possible although expensive (we expect that the cost to establish a drill rig to the location would be in excess of \$20,000 and daily drilling costs are likely to exceed \$5,000).

The most practical option may be to design the piles on the current stratigraphic information. In this case, the required depth to drive the piles would be finalised during installation. There would be a risk to the pile installation cost with this approach from the uncertainty in the depth to the higher strength material.

It must be noted that this approach would allow access only to the boat ramp and would not stabilise the nearby public areas, which would presumably have to remain closed until the stability of this area is acceptable.

## Limitations

Your attention is drawn to the document – "Limitations", which is attached to this report. The statements presented in this document are intended to advise you of what your realistic expectations of this report should be. The document is not intended to reduce the level of responsibility accepted by Golder Associates, but rather to ensure that all parties who may rely on this report are aware of the responsibilities each assumes in so doing.

## Closure

Should you have any queries regarding this letter, or if we can be of further assistance, please do not hesitate to contact this office.

**GOLDER ASSOCIATES PTY LTD**



Lyndon Sanders  
Principal Geotechnical Engineer

AJB/LJS/ed

Attachments: Limitations (LEG04, RL1)

i:\geo\2010\107662007 - dwlbc river murray lower reaches\correspondence out\107662007-011-l-rev0 caloote.docx

## LIMITATIONS

This Document has been provided by Golder Associates Pty Ltd ("Golder") subject to the following limitations:

This Document has been prepared for the particular purpose outlined in Golder's proposal and no responsibility is accepted for the use of this Document, in whole or in part, in other contexts or for any other purpose.

The scope and the period of Golder's Services are as described in Golder's proposal, and are subject to restrictions and limitations. Golder did not perform a complete assessment of all possible conditions or circumstances that may exist at the site referenced in the Document. If a service is not expressly indicated, do not assume it has been provided. If a matter is not addressed, do not assume that any determination has been made by Golder in regards to it.

Conditions may exist which were not detected given the limited nature of the enquiry Golder was retained to undertake with respect to the site. Variations in conditions may occur between assessment locations, and there may be special conditions pertaining to the site which have not been revealed by the investigation and which have not therefore been taken into account in the Document. Accordingly, additional studies and actions may be required.

In addition, it is recognised that the passage of time affects the information and assessment provided in this Document. Golder's opinions are based upon information that existed at the time the information is collected. It is understood that the Services provided allowed Golder to form no more than an opinion of the actual conditions of the site at the time the site was visited and cannot be used to assess the effect of any subsequent changes in the quality of the site, or its surroundings, or any laws or regulations.

Any assessments, designs, and advice provided in this Document are based on the conditions indicated from published sources and the investigation described. No warranty is included, either express or implied, that the actual conditions will conform exactly to the assessments contained in this Document.

Where data supplied by the client or other external sources, including previous site investigation data, have been used, it has been assumed that the information is correct unless otherwise stated. No responsibility is accepted by Golder for incomplete or inaccurate data supplied by others.

Golder may have retained subconsultants affiliated with Golder to provide Services for the benefit of Golder. To the maximum extent allowed by law, the Client acknowledges and agrees it will not have any direct legal recourse to, and waives any claim, demand, or cause of action against, Golder's affiliated companies, and their employees, officers and directors.

This Document is provided for sole use by the Client and is confidential to it and its professional advisers. No responsibility whatsoever for the contents of this Document will be accepted to any person other than the Client. Any use which a third party makes of this Document, or any reliance on or decisions to be made based on it, is the responsibility of such third parties. Golder accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this Document.